



Engineering Data Sheet: 2117

Unit Information

Model #: 2117 / Item # 13740
UPC-IC (12 Digit): 01673137403

Master Pack Dimensions

Weight: 4.9 lbs. (2.2 kg)
Cube: 0.39 ft³ (0.01 m³)
Quantity: 12

Specifications

Power Source: 2xD-cell
Alkaline or Carbon Zinc
Bulb/Lamp: PR-2
Bulb/Lamp Life: 15 Hours
Light Output: 10,000 Beam
Candlepower
Weight (Without batteries):
4.5 oz (.13 kg)

Components

Lens Ring: Polypropylene (Black)
Lens: Unbreakable Tuflexx®
Reflector: ABS
Tube: Polypropylene (Safety
Orange)
Contact Strip: Phosphor Bronze
Switch: Polyethylene
Bottom Cap: Polypropylene (Black)

Product Features

- For use in hazardous atmospheres
- Division 1 UL
- Lower cost of maintenance
- Crush Resistant Case
- Switch Guard
- 250,000 cycle positive locking switch
- Anti-roll tube
- Oversized, faceted reflector for more light
- Unbreakable Lens

Unit Dimensions

Length: 8.1 in. (20.6 cm)
Width: 2.3 in. (5.8 cm) at head
Height: N/A

Safety Approvals

UL Divisions 1 & 2
Class I, Group C & D
Class II, Group G
Class III
Operating Temp T4
ASTM & MSHA Approved



Worksafe Model # 2117

Accessories

23853
23860
20331

Description

6 1/2" Red Snap In Wand
6 1/2" Yellow Snap In Wand
PR2 Bulb

