380 Stewart Road Wilkes-Barre, PA 18706
PH: 570-825-1900
FAX: 570-825-7108

WorkSAFE Intrinsic ION Penlight
Product Data Sheet

P/N: Black _____60200
Green_____60201
Orange_____60202

Specifications

Power Source:	3 'AAAA' Alkaline Batteries
Light Source:	Seoul 'P9' Z-Power LED
LED Life:	10,000 hrs
Total Light Output:	25 Lumens
Projected Light Output:	255 Lux @ 3ft
Burn Time:	*20 Hours Continuous*
Operating Temperature Range:	-20C to 50C
H_2O resistance:	Watertight to 1m
Impact resistance:	survives 1m drop on to concrete
Weight:	1.5 oz (with batteries)
Length:	6.5 in.
Width:	0.65 in.
Height:	0.75 in.

Standard Product Features

- Deep Dish Parabolic Reflector
- On/Off Tail Switch
- Constructed of Super Tough Nylon
- Attachment Methods: Pocket Clip with neodymium magnet
- Embossed grip detail

Safety Certifications:

PENDING

Intrinsically Safe – Zone Zero

World Safety Standard:

IECEx Exia IIC T4 iaD T135C Ga, Da

EQUIVALENT to UL Rating:
Class I Division I Groups A, B, C, D
Class II Division I Groups E, F, G

ATEX II 1 GD Exia IIC T4 iaD T135C