

Engineering Data Sheet : 19101, 19102

Unit Information

Model #: 19101, 19102
 UPC-IC : 1673119101 / 02

Master Pack Dimensions

Weight: 7 lbs. 10 oz (3.46 kg)
 Cube: 1.03 ft³ (.03 m³)
 Cube Dimensions: 15.875" x 6.375" x 10.5"
 Quantity: 12 pcs.

Specifications

Power Source: 3 C Cell
 Bulb/Lamp: XPR3
 Bulb/Lamp Life: 30 Hours
 Light Output: 50,000 Beam Candlepower
 Weight (W/o batteries): 6.34 oz (.18 kg)
 Weight (w/ batteries) 16.3 oz (.46 kg)
 Replacement Bulb: XPR3 #20354
 Burn Time (continuous) 5 hours

Components

Lens Ring: Super-Tough Nylon w/ TPE
 Lens: Polycarbonate
 Reflector: Ultem 1000
 Tube: Super-Tough Nylon
 Contact Strip: Spring Steel
 Belt Clip: Super Tough Nylon
 Lanyard: Braided Nylon (Black)

Product Features

- Submersible to 100ft
- Non Conductive
- Limited Lifetime Warranty
- Passes 30 foot drop onto concrete
- Waterproof
- Pushbutton Switch
- Pre-focused spot beam
- 50,000 Candlepower, 5 hr continuous w/ alkaline batteries
- Key Ring, Lanyard, and Belt Clip Standard
- Self venting

Unit Dimensions

Length: 8.63 in. (21.92 cm)
 Width: 2.33 in. (5.91 cm) at head
 Height: N/A

Safety Approvals

UL: Class I, Div 1, Group D / Class I, Div 2, Group A, B, C & D
 Class II, Div 2, Group G
 Operating Temp T3A

MSHA Approved



<u>Part #'s:</u>	<u>Description</u>
19101	Orange Alkaline
19102	Yellow Alkaline

<u>Accessories</u>	<u>Description</u>
20354	XPR3 Bulb