

## ***2224LED Specifications***

### **Unit Information**

Model #: 2224LED / Item # 15720  
UPC-IC (12Digit): 016731157203

### **Unit Dimensions**

Length: 10.2 in. (25.1 cm)  
Width: 2.3 in. (5.8 cm) at head

### **Master Pack Dimensions**

Weight: 10.8 lbs. (4.9 kg)  
Cube: 1.43 ft<sup>3</sup> (0.04 m<sup>3</sup>)  
Quantity: 24

### **Safety Approvals**

UL Protection Methods  
Intrinsically Safe  
Divisions 1 & 2  
Class I, II, III Div 1 Groups A-G  
Class I, II, III Div 2 Groups A-G  
Operating Temp T5

### **Specifications**

Power Source: 3 x 'D' Cell Alkaline  
Light Source: LED  
Life: 30,000 hrs  
Runtime: 250 hrs  
Beam Distance: 88 meters  
Light Output: 50 Lumens  
Weight (Without batteries): 6.0 oz (.17 kg)

### **Product Features**

- For use in hazardous atmospheres
- 'S' Biner included for quick attachment
- Waterproof, IP 67 rating
- 'Switch Guard' prevents accidental lighting
- Anti-roll tube
- Faceted reflector for more light
- Three way switch: On-Momentary-Off



**WorkSafe™ Model #2224LED**

### **Accessories**

23853  
23860

### **Description**

6 ½" Red Snap In Wand  
6 ½" Yellow Snap In Wand

