

## Engineering Data Sheet : 200201, 200202, 200203

### Unit Information

UPC-IC: 16731 200201 (Orange)  
16731 200202 (Yellow)  
16731 200203 (Black)

### Unit Dimensions

Length: 6.7"  
Width: 2.34"  
Height: N/A

### Master Pack Dimensions

Weight: 5 lbs. .4 oz.  
Cube: 1.03 ft<sup>3</sup> (.03 m<sup>3</sup>)  
Cube Dimensions: 15.875" x 6.375" x 10.5"  
Quantity: 12 pcs.

### Specifications

Power Source: 2 C Cell  
Bulb/Lamp: Xenon  
Bulb/Lamp Life: 15 Hours  
Light Output: 30,000 Beam Candlepower  
Weight (Without batteries): 6.7 oz.  
Replacement Bulb: XPR2C #20351  
Approximate Burn time during continuous use: 5 hours 40 min.  
Approximate Burn time during intermittent use:  
6 hours 30 min.

### Components

Contact Strip: Brass  
Lanyard: Braided Nylon (Black)  
Belt Clip: Super-Tough Nylon  
Switch Boot: Thermoplastic Elastomer (TPE)  
Tube: Super-Tough Nylon  
Lens: Polycarbonate with Thermoplastic Elastomer (TPE)  
Reflector: Ultem 1000

### Product Features

- UL Division 1 & 2 Listed
- Non-Conductive
- Passes 30 foot drop onto concrete
- 30,000 Candlepower
- Pushbutton Switch
- Pre-focused spot beam
- Key-Ring Lanyard & Belt Clip Standard
- Lifetime Warranty
- Xenon Bulb
- Submersible 100ft

### Safety Approvals:

UL: Class I, Div 1, Group D / Class I, Div 2 Group A, B, C & D  
Class II, Div 2, Group G  
Operating Temp T3A

MSHA: Approved

When used with a KPR102, KPR104 or PR2

#### **Bulb:**

Class I, Div 1, Group C & D  
Operating Temp T3C



<u>Part #s</u>	<u>Description:</u>
200201	Orange
200202	Yellow
200203	Black
<u>Accessories</u>	<u>Description</u>
20351	XPR2C Bulb