

## Engineering Data Sheet: 2117

### Unit Information

Model #: 2117 / Item # 13740  
UPC-IC (12 Digit): 01673137403

### Master Pack Dimensions

Weight: 4.9 lbs. (2.2 kg)  
Cube: 0.39 ft<sup>3</sup> (0.01 m<sup>3</sup>)  
Quantity: 12

### Specifications

Power Source: 2xD-cell  
Alkaline or Carbon Zinc  
Bulb/Lamp: PR-2  
Bulb/Lamp Life: 15 Hours  
Light Output: 10,000 Beam  
Candlepower  
Weight (Without batteries):  
4.5 oz (.13 kg)

### Components

Lens Ring: Polypropylene (Black)  
Lens: Unbreakable Tuflexx®  
Reflector: ABS  
Tube: Polypropylene (Safety  
Orange)  
Contact Strip: Phosphor Bronze  
Switch: Polyethylene  
Bottom Cap: Polypropylene (Black)

### Product Features

- For use in hazardous atmospheres
- Division 1 UL
- Lower cost of maintenance
- Crush Resistant Case
- Switch Guard
- 250,000 cycle positive locking switch
- Anti-roll tube
- Oversized, faceted reflector for more light
- Unbreakable Lens

### Unit Dimensions

Length: 8.1 in. (20.6 cm)  
Width: 2.3 in. (5.8 cm) at head  
Height: N/A

### Safety Approvals

UL Divisions 1 & 2  
Class I, Group C & D  
Class II, Group G  
Class III  
Operating Temp T4  
ASTM & MSHA Approved



**Worksafe Model # 2117**

### Accessories

23853  
23860  
20331

### Description

6 1/2" Red Snap In Wand  
6 1/2" Yellow Snap In Wand  
PR2 Bulb

