

## ***Engineering Data Sheet : 2124***

### **Unit Information**

Model #: 2124 / Item # 14240  
UPC-IC (12 Digit): 01673142407

### **Master Pack Dimensions**

Weight: 5.1 lbs.  
Cube: 0.48 ft<sup>3</sup>  
Quantity: 12

### **Specifications**

Power Source: Carbon Zinc Only: 3xD-cell  
Bulb/Lamp: PR-7  
Bulb/Lamp Life: 15 Hours  
Light Output: 9,000 Beam Candlepower  
460 Candelas Peak Beam Intensity  
Weight (Without batteries): 6.0 oz (.17 kg)

### **Components**

Lens Ring: Polypropylene (Black)  
Lens: Unbreakable Tuflexx®  
Reflector: ABS  
Tube: Polypropylene (Safety Orange)  
Contact Strip: Phosphor Bronze  
Switch: Polyethylene  
Bottom Cap: Polypropylene (Black)  
Ring Hanger: ABS (Safety Orange)

### **Product Features**

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Lower cost of maintenance
- Crush Resistant Case
- Switch Guard
- 250,000 cycle positive locking switch
- Anti-roll Tube
- Oversized, faceted reflector for more light
- Unbreakable Lens

### **Unit Dimensions**

Length: 10.2 in. (25.1 cm)  
Width: 2.3 in. (5.8 cm) at head  
Height: N/A

### **Safety Approvals : Division 1 & 2**

UL/CUL: Class I, Div 1, Group C & D  
Class II, Div 1, Group G  
Class III  
Operating Temp T3C

ASTM & MSHA Approved



**WorkSafe Model # 2124**

### **Accessories**

23853  
23860  
20341

### **Description**

6 ½" Red Snap In Wand  
6 ½" Yellow Snap In Wand  
PR7 Bulb

