



2206LED Specifications

Unit Information

Model #: 2206 LED / Item #08050
UPC-IC (12 Digit): 016731080501

Master Pack Dimensions

Weight: 5.8 lbs. (2.6 kg)
Cube: 0.93 ft³ (0.02 m³)
Quantity: 6

Specifications

Power Source: 4 x 'D' Cell Alkaline
Light Source: LED
Life: 30,000 hrs
Runtime: 150 hrs
Light Output: 90 Lumens
Peak Beam Intensity: 7,000 Candela
Beam Distance: 165 meters
Impact Resistance: 1 meter

Product Features

- For use in hazardous atmospheres
- Waterproof, IP 67 rating
- 'D' Cell Alkaline Batteries
- Switch Guard protects switch on impact
- Glove friendly handle

Unit Dimensions

Length: 8.2 in. (20.9 cm)
Width: 4.9 in. (12.4 cm)
Height: 5.6 in. (14.2 cm)

Safety Approvals

UL Protection Methods
UL 913 CSA C22.2
Intrinsically Safe
Divisions 1 & 2
Class I, II, III Div 1 Groups A-G
Class I, II, III Div 2 Groups A-G
Operating Temp T5

Approved for use with:
Duracell MN1300
Energizer E95



WorkSafe™ Model # 2206LED

