



## Engineering Data Sheet : 19101, 19102

### Unit Information

Model #: 19101, 19102  
UPC-IC : 1673119101 / 02

### Master Pack Dimensions

Weight: 7 lbs. 10 oz (3.46 kg)  
Cube: 1.03 ft<sup>3</sup> (.03 m<sup>3</sup>)  
Cube Dimensions: 15.875" x 6.375" x 10.5"  
Quantity: 12 pcs.

### Specifications

Power Source: 3 C Cell  
Bulb/Lamp: XPR3  
Bulb/Lamp Life: 30 Hours  
Light Output: 50,000 Beam Candlepower  
Weight (W/o batteries): 6.34 oz (.18 kg)  
Weight (w/ batteries) 16.3 oz (.46 kg)  
Replacement Bulb: XPR3 #20354  
Burn Time (continuous) 5 hours

### Components

Lens Ring: Super-Tough Nylon w/ TPE  
Lens: Polycarbonate  
Reflector: Ultem 1000  
Tube: Super-Tough Nylon  
Contact Strip: Spring Steel  
Belt Clip: Super Tough Nylon  
Lanyard: Braided Nylon (Black)

### Product Features

- Submersible to 100ft
- Non Conductive
- Limited Lifetime Warranty
- Passes 30 foot drop onto concrete
- Waterproof
- Pushbutton Switch
- Pre-focused spot beam
- 50,000 Candlepower, 5 hr continuous w/ alkaline batteries
- Key Ring, Lanyard, and Belt Clip Standard
- Self venting

### Unit Dimensions

Length: 8.63 in. (21.92 cm)  
Width: 2.33 in. (5.91 cm) at head  
Height: N/A

### Safety Approvals

**UL:** Class I, Div 1, Group D / Class I, Div 2, Group A, B, C & D  
Class II, Div 2, Group G  
Operating Temp T3A

MSHA Approved



<u>Part #'s:</u>	<u>Description</u>
19101	Orange Alkaline
19102	Yellow Alkaline

<u>Accessories</u>	<u>Description</u>
20354	XPR3 Bulb

