



## Engineering Data Sheet: 2217

### Unit Information

Model #: 2217 / Item #14460  
UPC-IC (12 Digit): 01673144609

Unit Dimensions Length: 8.1 in. (20.6 cm) Width: 2.3 in. (5.8 cm) at head Height: N/A

### Master Pack Dimensions

Weight: 4.9 lbs. (2.2 kg)  
Cube: 0.39 ft<sup>3</sup> (0.01 m<sup>3</sup>)  
Quantity: 12

### Specifications

Power Source : Alkaline or Carbon Zinc:  
2xD-cell  
Bulb/Lamp: PR-2  
Run Time: 20 Hours  
Light Output: 10,000 Beam Candlepower  
Weight (Without batteries): 4.5 oz (.13 kg)

### Safety Approvals

UL Divisions 1 & 2  
Class I, Group C & D  
Class II, Group G  
Class III  
Operating Temp T5

ASTM & MSHA Approved

### Components

Lens Ring: Polypropylene (Black)  
Lens: Unbreakable Tuflexx®  
Reflector: ABS  
Tube: Polypropylene (Safety Orange)  
Contact Strip: Spring Brass & Tin Coated Steel  
Switch: Polypropylene  
Bottom Cap: Polypropylene (Black)



WorkSafe Model # 2217

### Product Features

- For use in hazardous atmospheres
- Waterproof IPX7
- Spare bulb compartment
- Circuit breaking mechanism
- Three-way switch : On-Off-Flash
- Anti-roll tube
- Oversized, faceted reflector for more light

### Accessories

<u>Accessories</u>	<u>Description</u>
23853	6 ½" Red Snap In Wand
23860	6 ½" Yellow Snap In Wand
20331	PR2 Bulb

