



380 Stewart Road Hanover Twp, PA 18706
 PH: 570-825-1900
 FAX: 570-825-7108

Lighthawk LED GEN II

Specifications:

Power Source:	4 Cell Lithium Ion Battery
LED Life:	30,000 Hours
Light Output:	300 Lumens High Mode / 125 Lumens Low Mode
Peak Beam Intensity:	70,000 Candela
Beam Distance:	447 M
Battery Run Time:	7 Hours High Mode / 14 Hours Low Mode
Impact Rating:	1 Meter
Weight:	1.9 lbs (with battery)
Length:	9.5 in.
Width:	3.12 in.
Height:	5.12 in.
Operating Temp Range:	- 20C to 50C

Output 300 LUMENS	Runtime 7H / 14H	Peak Beam Intensity 70,000 CD
Impact Resistance 1m	Beam Distance 447 M	Waterproof 1m

NFPA 1901-14.1.11.2 (2003) Certified Mounted in any Position

Standard Features:

- Wall and Vehicle Mountable
- Dual Mode Main Beam
High Mode / Low Mode
- Super Tough Nylon Construction
- LED charge Status Indicator
- Non-Slip rubber bottom and handle
- Low Battery Indicator
- Dual Mode High Visibility Signal Tail Light
Flashing Mode/ Steady Mode
- Easily adjustable articulated head
- Quick release shoulder strap
- Limited Lifetime warranty



Part #s:	Description
07610	4-cell, Orange, 120V AC
07610 UTIL	4-cell, Orange, 120V AC & 12/24V DC
07630	4-cell, Orange, 12/24V DC
07650	4-cell, Orange, 220V AC
07670	4-cell, Orange, Direct Wire
07612	4-cell, Yellow, 120V AC
07612 UTIL	4-cell, Yellow, 120V AC & 12/24V DC
07632	4-cell, Yellow, 12/24V DC
07652	4-cell, Yellow, 220V AC
07672	4-cell, Yellow, Direct Wire
07611	4-cell, Black, 120V AC
07611 UTIL	4-cell, Black, 120V AC & 12/24V DC
07631	4-cell, Black, 12/24V DC
07651	4-cell, Black, 220V AC
07671	4-cell, Black, Direct Wire

Safety Certification



Class I, II, III, Division 1, Groups C - G, T1
 Class I, II, III, Division 2, Groups A - G, T5
 -20°C to +50°C

Ingress Protection Level: IP67 1 meter

Accessories Description

9B-1962-1	4-Cell Replacement Lithium-Ion Battery
9B-1963-2	6-Cell Replacement Lithium-Ion Battery
07690	Charger Base
20628	120V AC Adapter
21132	Shoulder strap
21134	Seat Belt Style Strap
20629	220V Euro Cord
07870	12/24V DC Cord
3B-2033	Direct Wire Kit
10B-1926	Magnet Kit
10B-1926-I	Magnet Kit Installed

