







**WORKSAFE LED FLASHLIGHT
 EARNS THE HIGHEST GLOBAL
 SAFETY CERTIFICATIONS OFFERED
 AT THE MOST AFFORDABLE PRICE**

- ATEX/IECex- Zone 0
- Intrinsically Safe
- Waterproof, IP67 rating
- Three-way switch : On-Momentary-Off
- 'Switch Guard' Prevents accidental lighting
- Impact resistant to one meter
- Tail cap slot for lanyard



**WATERPROOF FLASHLIGHT RUNS FOR
 200 HRS BEFORE BATTERIES NEED REPLACING.**

FL1 STANDARDS

SPECIFICATIONS

POWER SOURCE: 2 D-Cell Alkaline Batteries
LIGHT SOURCE: LED
LIGHT OUTPUT: 80 Lumens
PEAK BEAM INTENSITY: 2,450 candela
BEAM DISTANCE: 100 Meters
RUN TIME: 200 Hours

MASTER PACK

WEIGHT: 5 oz. without batteries
LENGTH: 1.43 ft. **WIDTH:** 1.43 ft. **DEPTH:** 1.43 ft.
COLORS: Black Housing, Safety Orange Lens Rim
UPC-IC (12 Digit): 016731164607

SAFETY RATINGS

IECEx protection Methods	UL protection Methods
Ex ia IIB T3 Ga	Intrinsically Safe Division 1 and 2
Ex ia IIIB T145°C Da	Class I, II, III Div 1 Groups A-G
-5°C ≤ +40°C	Class I, II, III Div 2 Groups A-G
ATEX protection Methods	T5
Ex II 1GD Ex ia IIB T3 Ga	
Ex ia IIIB T145°C Da -5°C ≤ Ta ≤ +40°C	
Zone 0	

*Safety approvals based on Duracell MN1300 or Energizer E95 cells only

MODEL

#16460-2217 LED ATEX

ACCESSORIES

#23853 - 6 1/2" Red Snap In Wand

#23860 - 6 1/2" Yellow Snap In Wand

