







**WORKSAFE LED LANTERN  
 EARNS THE HIGHEST GLOBAL  
 SAFETY CERTIFICATIONS OFFERED  
 AT THE MOST AFFORDABLE PRICE**

- Intrinsically Safe
- Waterproof, IP 67 rating
- D' Cell Alkaline Batteries
- Switch Guard protects switch on impact
- Glove friendly handle
- ATEX / IECEx Rating Info: 2206 LED ATEX – Zone 1



**LIGHTWEIGHT, LONG RUNNING  
 LANTERN FOR ILLUMINATION  
 IN HAZARDOUS ENVIRONMENTS**

**FL1 STANDARDS**

 90 LUMENS	 150 h
 7,000 cd	 1m
 165m	 1m


**SPECIFICATIONS**

**POWER SOURCE:** 4 D-Cell Alkaline Batteries  
**LIGHT SOURCE:** LED  
**LIGHT OUTPUT:** 90 Lumens  
**PEAK BEAM INTENSITY:** 7,000 candela  
**BEAM DISTANCE:** 165 Meters  
**RUN TIME:** 150 Hours (alkaline batteries)

**MASTER PACK**

**WEIGHT:** 5.8 lbs with alkaline battery pack  
**LENGTH:** 8.2 in. **WIDTH:** 4.9 in. **Height:** 5.6 in.  
**COLORS:** Black Housing, Safety Orange Lens Rim

**SAFETY RATINGS**

<b>IECEx protection Methods</b>	<b>UL protection Methods</b>
Ex ib IIB T3 Gb	Intrinsically Safe Division 1 and 2
Ex ib IIIB T180°C Db	Class I, II, III Div 1 Groups A-G
-5°C ≤ +40°C	Class I, II, III Div 2 Groups A-G
<b>ATEX protection Methods</b>	T5
 II 2GD Ex ib IIB T3 Gb	
Ex ib IIIB T180°C Db -5°C ≤ Ta ≤ +40°C	
<b>Zone 1</b>	

\*Safety ratings approvals based on Duracell MN1300 or Energizer E95 cells only