



## Engineering Data Sheet : 200301

### Unit Information

UPC-IC : 16731200301 (orange)

### Master Pack Dimensions

Weight: 3 lbs.

Cube: 1.03 ft<sup>3</sup> (.03 m<sup>3</sup>)

Cube Dimensions: 10.06" x 5.625" x 10.5"

Quantity: 12 pcs.

### Specifications

Power Source: 2 AA Cells

Bulb/Lamp: Xenon

Bulb/Lamp Life: 15 Hours

Light Output: 13,000 Beam Candlepower

Weight (Without batteries): 2.2 oz.

Replacement Bulb: XPR2AA #20350

Approximate Burn time during continuous use: 3 hours 30 min.

Approximate Burn time during intermittent use: 4 hours 30 min.

### Components

Lens: Polycarbonate with Thermoplastic Elastomer (TPE)

Reflector: Ultem 1000

Tube: Super Tough Nylon

Contact Strip: Spring Brass

Switch Boot: Thermoplastic Elastomer (TPE)

### Product Features

- UL Division 1 & 2 Listed
- Non-Conductive
- Passes 30 foot drop onto concrete
- 13,000 Candle Power
- Pushbutton Switch
- Pre-focused spot beam
- Key Ring
- Lifetime Limited Warranty
- Xenon Bulb
- Submersible to 100ft
- Pocket size
- Fits Helmet Clips

### Unit Dimensions

Length: 6.65"

Width: 1.42"

Height: 1.4

### Safety Approvals

UL: Class I, Div 1, Group C & D / Class I, Div 2 Group A, B, C, D  
Class II, Div 2, Group G  
Operating Temp T3C

MSHA: Approved



### Part #'s

200301

### Description:

Orange

20350

XPR2AA Bulb

