



## Engineering Data Sheet: 2224

### Unit Information

Model #: 2224 / Item # 14720  
UPC-IC (12 Digit): 01673147204

### Master Pack Dimensions

Weight: 5.8 lbs. (2.6 kg)  
Cube: 0.48 ft<sup>3</sup> (0.014 m<sup>3</sup>)  
Quantity: 12

### Specifications

Power Source : Carbon Zinc Only: 3xD-cell  
Bulb/Lamp: PR-3  
Bulb/Lamp Life: 15 Hours  
Light Output: 15,000 Beam Candlepower  
770 Candelas Peak Beam Intensity  
Weight (Without batteries): 6.0 oz (.17 kg)

### Components

Lens Ring: Polypropylene (Black)  
Lens: Unbreakable Tuflexx®  
Reflector: ABS  
Tube: Polypropylene (Safety Orange)  
Contact Strip: Spring brass & tin steel  
Switch: Polypropylene  
Bottom Cap: Polypropylene (Black)

### Product Features

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Waterproof IPX7
- Three-way switch : On-Off-Flash
- Anti-roll tube
- Oversized, faceted reflector for more light
- Circuit breaking mechanism

### Accessories

<u>Accessories</u>	<u>Description</u>
23853	6 ½" Red Snap In Wand
23860	6 ½" Yellow Snap In Wand
20332	PR3 Bulb

### Unit Dimensions

Length: 10.2 in. (25.1 cm)  
Width: 2.3 in. (5.8 cm) at head  
Height: N/A

### Safety Approvals

UL/CUL: Class I, Div 1, Group C & D  
Class II, Div 1, Group G

ASTM & MSHA: Approved



**WorkSafe™ I Model  
#2224**

